

## Clipped Sinewave 4 Pad SMD

- Industry-standard SMD package 11.4 x 9.6 x 3.0mm
- Close tolerance stabilities from  $\pm 0.5\text{ppm}$  over  $0^\circ$  to  $+50^\circ\text{C}$
- $\pm 1\text{ppm}$  over  $-40$  to  $+85^\circ\text{C}$
- Low power consumption

### DESCRIPTION

M43S series TCXOs are packaged in the industry-standard 11.4 x 9.6 x 4.7mm SMD package. With clipped sinewave output, close tolerances are available from  $\pm 0.5\text{ppm}$  over  $0^\circ$  to  $50^\circ\text{C}$  or  $\pm 1\text{ppm}$  over  $-40^\circ$  to  $+85^\circ\text{C}$ . The part has low power consumption.

### SPECIFICATION

Product Series Code	TCXO:	M43S
	VCTCXO:	VM43S
Frequency Range:	10.0MHz to 27.0MHz	
Output Waveform:	Clipped Sinewave	
Initial Calibration Tolerance:	$< \pm 1\text{ppm}$ at $25^\circ\text{C}$	
Standard Frequencies:	10.0, 12.80, 13.0, 14.40, 15.36, 16.384, 19.2, 19.440, and 19.68MHz (Partial list)	
Operating Temperature Range:	See table	
Frequency Stability		
vs. Ageing:	$\pm 1.0\text{ppm}$ max. first year	
vs. Voltage Change:	$\pm 0.3\text{ppm}$ max. $\pm 5\%$ change	
vs. Load Change:	$\pm 0.3\text{ppm}$ max. $\pm 10\%$ change	
vs. Reflow:	$\pm 1\text{ppm}$ max. for one reflow (Measured after 24 hours)	
Supply Voltage:	$+2.8, +3.0$ or $+5.0\text{Volts}$ (Specify when ordering)	
Output Voltage Level:	0.8V p-p minimum	
Start-up Time:	2ms typical, 5ms max.	
Current Consumption:	See table below	
Output Load:	10k $\Omega$ /10pF $\pm 10\%$	
Harmonic Distortion:	-10dB typical, -7dB max.	
SSB Phase Noise:	See table	
Output Format:	DC block, AC coupled	
Storage Temperature:	$-50^\circ$ to $+100^\circ\text{C}$	
RoHS Status:	RoHS Compliant version available. See part numbering procedure.	


### FREQUENCY STABILITY

Frequency Stability (ppm)		$\pm 0.5$	$\pm 1.0$	$\pm 1.5$	$\pm 2.0$	$\pm 2.5$
Temperature Range ( $^\circ\text{C}$ )	0 ~ +50	ASK	✓	✓	✓	✓
	-10 ~ +60	x	✓	✓	✓	✓
	-20 ~ +70	x	x	✓	✓	✓
	-30 ~ +75	x	x	x	✓	✓
	-40 ~ +85	x	x	x	x	✓


✓ = available, x = not available, ASK = call Technical Sales

### CURRENT CONSUMPTION

Supply Voltage		Max Current	
		+3.0V	+5.0V
Frequency Range	10.0 to 13MHz	1.3mA	2.0mA
	13.01 to 20MHz	1.5mA	2.2mA
	20.01 to 27MHz	2.0mA	2.5mA



### M43S - OUTLINES AND DIMENSIONS



### VM43S VOLTAGE CONTROL SPECIFICATION

Control Voltage:	Standard = $+1.5 \pm 1.0\text{Volts}$ for all input voltages. (Contact technical sales if $+2.5 \pm 2.0\text{Volts}$ is required.)
Frequency Deviation:	$\pm 6.0\text{ppm}$ min.
Slope Polarity:	Positive (increase of control voltage increases output frequency.)
Input Impedance:	1.0M $\Omega$ min.
Modulation Bandwidth:	3.0kHz min. measured at -3dB

### PHASE NOISE

SSB Phase Noise at $25^\circ\text{C}$	Offset (Hz)	10	100	1k	10k	100k
	M325 13MHz (dBc/Hz)		-80	-115	-135	-148

### PART NUMBERING PROCEDURE

