

Temperature Compensated Crystal Oscillators [TCXO " M " and VCTCXO " VM "] CMOS Output

TCXO	VCTCXO	MHz range	CMOS	SMD	15pF	2.5 V	3.0 V	Min.	Max.
ML _ T	VML _ T					3.3 V	5.0 V	40 MHz	156 MHz

Features

- High frequency range : [40.0 MHz ~ 156.0 MHz]
- Frequency stability as tight as ± 0.5 ppm over 0°C to 50°C
Frequency stability as tight as ± 1.0 ppm over -40°C to 85°C



General specifications of all available packages , at $T_a=+25^{\circ}\text{C}$, $C_L=15\text{pF}$

Output Wave Form		Square wave [LVCMOS] . Wave form code is " T "					
Type	ML572T , VML572T			ML43T , VML43T			
Package (Size)	(7.0 x 5.0 x 2.6 mm)			(11.4 x 9.6 x 3.1 mm)			
Frequency Range	40.0 ~ 156.0 MHz			40.0 ~ 156.0 MHz			
Input Voltage Range	Standard	+2.5 V (code is " 25 ")	+3.0 V (code is " 3 ")	+3.3 V (code is " 33 ")	+5.0 V (code is " 5 ")		
Initial Calibration Tolerance	Models with mechanical trimmer : $< \pm 1.0$ ppm. $+25^{\circ}\text{C} \pm 2^{\circ}\text{C}$. Models without mechanical trimmer : ± 2.0 ppm at $+25^{\circ}\text{C} \pm 2^{\circ}\text{C}$.						
Frequency Stability (ppm)		± 0.5 ppm	± 1.0 ppm	± 1.5 ppm	± 2.0 ppm	± 2.5 ppm	± 3.0 ppm
Frequency Stability vs Temperature (examples)	0°C to 50°C	○	○	○	○	○	○
	-10°C to 60°C	△	○	○	○	○	○
	-20°C to 70°C	X	○	○	○	○	○
	-30°C to 75°C	X	○	○	○	○	○
	-30°C to 85°C	X	○	○	○	○	○
Frequency Stability	vs Aging	± 1.0 ppm max., per year at 25°C .					
	vs Voltage Change	± 0.3 ppm max. , for a $\pm 5\%$ input voltage change .					
	vs Load Change	± 0.3 ppm max. , for a $\pm 10\%$ load condition change .					
	vs Reflow (SMD type)	± 1.0 ppm max., 1 reflow and measured 24 hours afterwards .					
Output Voltage Level (peak to peak)	T T L / CMOS						
Output Logic Levels	Logic High " 1 " : 90% of V_{DD} min.			Logic High " 0 " : 10% of V_{DD} min.			
Mechanical Frequency Tuning	Standard	± 3.0 ppm (min.) tuning					
		Note: VM57 has no mechanical trimmer built-in.					
	Option	No mechanical trimmer built-in (for aqueous washing cycles). To order please add " 1 " after the regular model prefix . Example: M381T.					
Current Consumption (Over operating temperature range)		77.760 MHz 32 mA (max.)	155.520 MHz 50 mA (max.)				
Electrical Frequency Tuning (EFC) by external control voltage	Control Voltage Center	Standard: $+1.5\text{ V} \pm 1.0\text{ V}$ for all input voltages.					
	Frequency Deviation Range	± 5.0 ppm. (min.) with $V_{con} = +1.5\text{ V} \pm 1.0\text{ V}$					
	Slope Polarity (Transfer Function)	Positive slope. Positive voltage for positive frequency shift.					
		Input Impedance : 50M Ω min.	Modulation Bandwidth : 20 KHz min.	Linearity : $\pm 10\%$ max.			
Rise Time and fall time	10.0 n sec. max.; 20% \leftrightarrow 80% of the wave form.						
Duty Cycle	Standard: 50 % $\pm 10\%$; Option: 50 % $\pm 5\%$						
Start-Up Time.	5.0 m sec. (typ.) , 10.0 m sec. (max.) (reach 90% amplitude and at $+25^{\circ}\text{C} \pm 2^{\circ}\text{C}$)						
Output Load	15 pF						
SSB Phase Noise at 25°C , 15pF	Offset / dBc / Hz [typical]	10 Hz	100 Hz	1 KHz	10 KHz	100 KHz	
	M572T33 - 77.760	-74 dBc / Hz	-99 dBc / Hz	-98 dBc / Hz	-95dBc / Hz	-90 dBc / Hz	
	M572T33 - 155.520	-68 dBc / Hz	-96 dBc / Hz	-100 dBc / Hz	-99 dBc / Hz	-90 dBc / Hz	
Storage Temperature	-40°C to $+85^{\circ}\text{C}$ or -55°C to $+125^{\circ}\text{C}$ (package dependent)						

TCXOs

Mercury www.mercury-crystal.com

■ Taiwan : Tel:(+886)-2-2406-2779 / sales-tw@mercury-crystal.com

■ USA: Tel: (+1)-909-466-0427 / sales-us@mercury-crystal.com

■ China: Tel: (+86)-512-5763-8100 / sales-cn@mercury-crystal.com